

10 KVA Tower Mount UP

Features


- N+X parallel redundancy, support maximum 4 units in parallel
- Online double conversion with full digital control
- Optimization battery group, the quantity of battery: 16/18/20pcs (Settable)
- Wide input voltage range: 110~286Vac
- Wide input frequency range
- Selectable output voltage: 208/220/230/240Vac
- Generator compatible
- ECO mode operation for energy saving
- Self-testing when UPS startup
- Multiple communication interface: RS232/USB/EPO (Relay card /SNMP card optional)
- Maximum charging current up to 10A
- Cold start
- Design with maintenance switch (Optional)
- Intelligent fan speed regulation
- Multiple protection function: short-circuit, overload, overheat, battery overcharge and overdischarge, output low voltage and fan fault alarm



Parallel board



Colorful Lcd



Relay card



SNMP



10 KVA Tower Mount UP

Technical specification



MODEL	Titanium PETA POWER 10 KVA ONLINE 1-1 Phase
Capacity	10 KVA / 10000 W
INPUT	
Nominal voltage	208/220/230/240Vac
Input voltage range	110~286Vac
Frequency range	40~70Hz (50/60Hz Auto-Sensing)
Power factor	≥0.99
Bypass voltage range	"Max.voltage:220V:+25% (Optional+10%,15%,20%) 230V:+20% 240V:+15% Min.voltage:-45%"
OUTPUT	
Output voltage	208/220/230/240Vac
Power factor	1
Voltage regulation	±1%
"Output frequency"	"Line Mode :±10% of the rated frequency Bat. Mode :(50/60±0.1%)Hz"
Crest factor	3:1
Harmonic distortion (THDv)	"≤2% Linear load ≤5% Non linear load"
Transfer time	0ms
Output waveform	Pure Sinewave
Overload	"Line Mode :Load≤110% last 60min; ≤125% last 10min; ≤150% last 1min;>150% turn to bypass mode immediately Bypass Mode : 63A (Breaker)"
EFFICENCY	
EFFICENCY	94%
BATTERIES	
Battery number	(±96/±108/±120Vdc (Adjustable)
Inbuilt battery	12V/9Ah x16
Charging current (Max)	1A
Recharge time	6-8 hours (to 90% of full capacity)
INDICATORS	
LCD display	Input voltage,Input frequency,Output voltage,Output frequency,Load percentage, Battery voltage,Inner temperature& Remaining battery backup time
ALARM	
Battery mode	Beeping every 4 seconds
Low Battery	Beeping every second
Overload	Beeping twice every second
Fault	Continuously beeping
ENVIRONMENT	
Operating temperature	0 ~40
Storage temperature	-25 ~55
Humidity range	20-95%RH @ 0-40 (Non condensing)
Altitude	<1500m,derating required when>1500m
Noise level	<58dB at 1 Meter
STANDARDS	
Safety	IEC/EN62040-1,IEC/EN62477-1
EMC	IEC/EN62040-2,IEC61000-4-2,IEC61000-4-3,IEC61000-4-4,IEC61000-4-5,IEC61000-4-6,IEC61000-4-8
PHYSICAL	
Dimension W x D×H (mm)	191 x 460 x 720 (With wheel)
Net weight (kg)	71.5

"Specifications are subject to change without prior notice."